


DIAMOND INCLINE – TAN BELTING



Description:	2 PLY APT75 TAN SYN DIAXTD (S50)
Product Number	24-72-2079-722
Product Construction	Diamond X Treated Duck (Natural/Synthetic on Treated Polyester Fabric)
Color	Tan
Compound Formulation	Natural/Synthetic
Fabric	Treated Polyester
Nominal Overall Gauge, inches	0.290 ± 0.031
mm	7.4 ± 0.8
Nominal Weight, lbs./ft2	1.27 ±10%
kg/m2	6.20 ±10%
Rated Working Tension, lbs./inch	150
N/mm	26
Top Cover Surface	Diamond Incline
Bottom Cover Surface	RFL treated fabric
Minimum Pulley Diameter, inches	4.0
mm	101.0
Temperature Range	-30° to +180°F -34° to +82°C
Cover Coefficient of Friction, Steel	1.0 nominal
Cardboard	1.0 nominal
Bottom Coefficient of Friction, Steel	0.30 max
Cardboard	0.32 max
Available Width(s)	72"
Typical Applications	General Incline/Decline conveying > 5%

Phone: 800-367-0420 Email: info@hbdthermoid.com www.hbdthermoid.com
 Corporate Sales & Customer Service: 800-543-8070

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.