

### GRIPTOP™ – BLACK BELTING



*representative image*

<b>Description:</b>	3 PLY PCB35+ BLK SYN RTXFS (S0)
<b>Product Number</b>	24-92-0139-722
<b>Product Construction</b>	Rough Top X Friction (Black Synthetic on Polyester & Cotton/Polyester Fabric)
<b>Color</b>	Black
<b>Compound Formulation</b>	Synthetic
<b>Fabric</b>	Polyester & Cotton/Polyester
<b>Nominal Overall Gauge, inches</b>	0.300 ± 0.031
<b>mm</b>	7.6 ± 0.8
<b>Nominal Weight, lbs./ft<sup>2</sup></b>	1.12 ±10%
<b>kg/m<sup>2</sup></b>	5.47 ±10%
<b>Rated Working Tension, lbs./inch</b>	105
<b>N/mm</b>	18
<b>Top Cover Surface</b>	Roughtop
<b>Bottom Cover Surface</b>	Friction
<b>Minimum Pulley Diameter, inches</b>	4
<b>mm</b>	101
<b>Temperature Range</b>	-30° to +180°F -34° to +82°C
<b>Cover Coefficient of Friction, Steel</b>	1.0 nominal
<b>Cardboard</b>	1.0 nominal
<b>Bottom Coefficient of Friction, Steel</b>	0.30 to 0.35 max
<b>Cardboard</b>	0.35 to 0.40 max
<b>Available Width(s)</b>	72"
<b>Typical Applications</b>	Package Handling/Incline Service

Phone: 800-367-0420    Email: [info@hbdthermoid.com](mailto:info@hbdthermoid.com)    [www.hbdthermoid.com](http://www.hbdthermoid.com)  
 Corporate Sales & Customer Service: 800-543-8070

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.