


GRIPTOP™ – BLUE BELTING



Description:	3 PLY PNT50 BLU XNBR RTXTD (S20)
Product Number	24-12-3441-722
Product Construction	Roughtop X Treated Duck (Blue Carboxylate Nitrile on Treated Polyester/Nylon Fabric)
Color	Blue
Compound Formulation	Carboxylate
Fabric	Treated Polyester/Nylon
Nominal Overall Gauge, inches	0.297 ± 0.031
mm	7.5 ± 0.8
Nominal Weight, lbs./ft2	1.15 ±10%
kg/m2	5.61 ±10%
Rated Working Tension, lbs./inch	150
N/mm	26
Top Cover Surface	Roughtop
Bottom Cover Surface	Treated Duck
Minimum Pulley Diameter, inches	4
mm	101
Temperature Range	20° to +212°F -7° to +100°C
Cover Coefficient of Friction, Steel	1.0 nominal
Cardboard	1.0 nominal
Bottom Coefficient of Friction, Steel	0.30 max
Cardboard	0.32
Available Width(s)	72"
Typical Applications	General Incline/Decline conveying > 5%

Phone: 800-367-0420 Email: info@hbdthermoid.com www.hbdthermoid.com
 Corporate Sales & Customer Service: 800-543-8070

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.