


GRIPTOP™ – TAN BELTING



| | |
|--|---|
| Description: | 2 PLY APT60 TAN SYN RTXTD (S30) |
| Product Number | 24-69-2452-722 |
| Product Construction | Roughtop X Treated Duck (Tan Natural/SBR on Treated Polyester Fabric) |
| Color | Tan |
| Compound Formulation | Natural/SBR |
| Fabric | Treated Polyester |
| Nominal Overall Gauge, inches | 0.249 ± 0.031 |
| mm | 6.3 ± 0.8 |
| Nominal Weight, lbs./ft² | 1.00 ±10% |
| kg/m² | 4.88 ±10% |
| Rated Working Tension, lbs./inch | 150 |
| N/mm | 26 |
| Top Cover Surface | Roughtop |
| Bottom Cover Surface | RFL treated fabric |
| Minimum Pulley Diameter, inches | 2.5 |
| mm | 64 |
| Temperature Range | -20° to +180°F -29° to +82°C |
| Cover Coefficient of Friction, Steel | 1.0 nominal |
| Cardboard | 1.0 nominal |
| Bottom Coefficient of Friction, Steel | 0.30 max |
| Cardboard | 0.32 max |
| Available Width(s) | 72" |
| Typical Applications | General Incline/Decline conveying > 5% |

Phone: 800-367-0420 Email: info@hbdthermoid.com www.hbdthermoid.com
 Corporate Sales & Customer Service: 800-543-8070

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.