

HOT N COLD – WHITE BUTYL BELTING



Description:	3 PLY APT35 WHT BUTYL 1/32XFS (S10) (1,2) HOT/COLD
Product Number	24-24-3721-722
Product Construction	Smooth X Friction (White Butyl on Treated Polyester Fabric)
Color	White
Compound Formulation	Butyl
Fabric	Treated Polyester
Nominal Overall Gauge, inches	0.112 ± 0.020
mm	2.8 ± 0.50
Nominal Weight, lbs./ft²	0.75 ±10%
kg/m²	3.66 ±10%
Rated Working Tension, lbs./inch	105
N/mm	18
Top Cover Surface	Smooth
Bottom Cover Surface	Friction
Minimum Pulley Diameter, inches	2 (4 below 0 °F)
mm	51 (101 below -18°C)
Temperature Range	-65° to +300°F -54° to +149°C
Special Standards	USDA/FDA Approved
Cover Coefficient of Friction, Steel	1.0 nominal
Cardboard	1.0 nominal
Bottom Coefficient of Friction, Steel	0.30 to 0.35
Cardboard	0.35 to 0.40
Available Width(s)	72"
Typical Applications	Hot Food

Phone: 800-367-0420 Email: info@hbdthermoid.com www.hbdthermoid.com

Corporate Sales & Customer Service: 800-543-8070

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.