


### HOT STOCK & WATER – BLACK BELTING



<b>Description:</b>	3 Ply PCB35/300Z BLK SYN SHDXFS (S8) HS&W
<b>Product Number</b>	24-55-3011-722
<b>Product Construction/Plies</b>	Silver Hard Duck X Friction (Black Synthetic on Polyester/Cotton Fabrics)
<b>Color</b>	Black
<b>Compound Formulation</b>	Synthetic
<b>Fabric</b>	Polyester/Cotton
<b>Nominal Overall Gauge, inches</b>	0.145 ± 0.020
<b>mm</b>	3.7 ± 0.50
<b>Nominal Weight, lbs./ft2</b>	0.59 ±10%
<b>kg/m2</b>	2.88 ±10%
<b>Rated Working Tension, lbs./inch</b>	105
<b>N/mm</b>	18
<b>Top Cover Surface</b>	Silver Hard Duck
<b>Bottom Cover Surface</b>	Friction
<b>Minimum Pulley Diameter, inches</b>	4
<b>mm</b>	101
<b>Temperature Range</b>	-20° to +250°F -29° to +121°C
<b>Cover Coefficient of Friction, Steel</b>	NA
<b>Cardboard</b>	NA
<b>Bottom Coefficient of Friction, Steel</b>	0.30 to -0.35 max
<b>Cardboard</b>	0.35 to -0.40 max
<b>Available Width(s)</b>	72"
<b>Typical Applications</b>	Hot Rubber

Phone: 800-367-0420    Email: [info@hbdthermoid.com](mailto:info@hbdthermoid.com)    [www.hbdthermoid.com](http://www.hbdthermoid.com)  
 Corporate Sales & Customer Service: 800-543-8070

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.