


HOT STOCK & WATER – BLACK BELTING



Description:	3 Ply PCB35/300Z BLK SYN SHDXFS (S8) HS&W
Product Number	24-55-4011-722
Product Construction	Silver Hard Duck X Friction (Black Synthetic on Polyester & Cotton Fabrics)
Color	Black
Compound Formulation	Synthetic
Fabric	Polyester & Cotton
Nominal Overall Gauge, inches	0.194 ± 0.031
mm	4.9 ± 0.8
Nominal Weight, lbs./ft²	0.94 ±10%
kg/m²	4.59 ±10%
Rated Working Tension, lbs./inch	140
N/mm	25
Top Cover Surface	Silver Hard Duck
Bottom Cover Surface	Friction
Minimum Pulley Diameter, inches	6
mm	152
Temperature Range	-20° to +250°F -29° to +121°C
Cover Coefficient of Friction, Steel	NA
Cardboard	NA
Bottom Coefficient of Friction, Steel	0.30 to -0.35 max
Cardboard	0.35 to -0.40 max
Available Width(s)	72"
Typical Applications	Hot Rubber

Phone: 800-367-0420 Email: info@hbdthermoid.com www.hbdthermoid.com
 Corporate Sales & Customer Service: 800-543-8070

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.