

### HOT STOCK & WATER – RED BELTING



<b>Description:</b>	3 PLY PCB35 BLK SYN SILXFS (S8) RED SILICONE TOP HS&W
<b>Product Number</b>	24-55-3018-602
<b>Product Construction</b>	Silicone X Friction (Black Synthetic on Polyester/Cotton Fabric)
<b>Color</b>	Red
<b>Compound Formulation</b>	Synthetic
<b>Fabric</b>	Polyester/Cotton
<b>Nominal Overall Gauge, inches</b>	0.152 ± 0.020
<b>mm</b>	3.9 ± 0.5
<b>Nominal Weight, lbs./ft<sup>2</sup></b>	0.65 ±10%
<b>kg/m<sup>2</sup></b>	3.17 ±10%
<b>Rated Working Tension, lbs./inch</b>	105
<b>N/mm</b>	18
<b>Top Cover Surface</b>	Red Silicone
<b>Bottom Cover Surface</b>	Friction
<b>Minimum Pulley Diameter, inches</b>	4
<b>mm</b>	101
<b>Temperature Range</b>	-20° to +350°F (top cover) -29° to +177°C (top cover)
<b>Cover Coefficient of Friction, Steel</b>	NA
<b>Cardboard</b>	NA
<b>Bottom Coefficient of Friction, Steel</b>	0.30 max
<b>Cardboard</b>	0.25 max
<b>Available Width(s)</b>	60"
<b>Typical Applications</b>	Hot Materials

Phone: 800-367-0420    Email: [info@hbdthermoid.com](mailto:info@hbdthermoid.com)    [www.hbdthermoid.com](http://www.hbdthermoid.com)  
 Corporate Sales & Customer Service: 800-543-8070

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.