

NITRILE – BLACK BELTING



Description:	4 PLY PNT50 BLK NBR 3/32XTD (S15)
Product Number	24-59-4034-722
Product Construction	Smooth X Treated Duck (Black Nitrile on Polyester/Nylon Fabric)
Color	Black
Compound Formulation	Nitrile
Fabric	Polyester/Nylon
Nominal Overall Gauge, inches	0.250 ± 0.031
mm	6.4 ± 0.8
Nominal Weight, lbs./ft²	1.46 ±10%
kg/m²	7.13 ±10%
Rated Working Tension, lbs./inch	180
N/mm	32
Top Cover Surface	Smooth
Bottom Cover Surface	Treated Duck
Minimum Pulley Diameter, inches	4
mm	102
Temperature Range	20° to +212°F -7° to +100°C
Cover Coefficient of Friction, Steel	NA
Cardboard	NA
Bottom Coefficient of Friction, Steel	0.20 to 0.25 max
Cardboard	
Available Width(s)	72"
Typical Applications	General Trade

Phone: 800-367-0420 Email: info@hbdthermoid.com www.hbdthermoid.com
 Corporate Sales & Customer Service: 800-543-8070

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.