


RIDGETOP™ – WHITE BELTING



Description:	3 PLY PNT50 WHT NBR RD/TPXFS (S10) (1,2) SANI-BRITE
Product Number	24-28-3829-722
Product Construction	Ridgetop X Friction (White Nitrile on Treated Polyester Fabric)
Color	White
Compound Formulation	Nitrile
Fabric	Treated Polyester
Nominal Overall Gauge, inches	0.0290 ± 0.031
mm	7.4 ± 0.8
Nominal Weight, lbs./ft²	1.25 ±10%
kg/m²	6.10 ±10%
Rated Working Tension, lbs./inch	150
N/mm	26
Top Cover Surface	Ridgetop
Bottom Cover Surface	Friction
Minimum Pulley Diameter, inches	3
mm	76
Temperature Range	20° to +212°F -6° to +100°C
Special Standards	USDA/FDA Approved
Cover Coefficient of Friction, Steel	1.0 nominal
Cardboard	1.0 nominal
Bottom Coefficient of Friction, Steel	0.30 max
Cardboard	0.32 max
Available Width(s)	72'
Typical Applications	Food Handling incline up to 30

Phone: 800-367-0420 Email: info@hbdthermoid.com www.hbdthermoid.com
 Corporate Sales & Customer Service: 800-543-8070



PRODUCT SPECIFICATIONS

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.