

### SANI-BRIGHT™ – WHITE BELTING



<b>Description:</b>	3 PLY PNT50 WHT NBR 0.04XFS (S10) (1,2) SANI-BRITE	
<b>Product Number</b>	24-91-3021-722	
<b>Product Construction</b>	Smooth X Friction (White Nitrile on Treated Polyester Fabric)	
<b>Color</b>	White	
<b>Compound Formulation</b>	Nitrile	
<b>Fabric</b>	Treated Polyester	
<b>Nominal Overall Gauge, inches</b>	0.135 ± 0.020	
<b>mm</b>	3.4 ± 0.5	
<b>Nominal Weight, lbs./ft<sup>2</sup></b>	0.83 ±10%	
<b>kg/m<sup>2</sup></b>	4.05 ±10%	
<b>Rated Working Tension, lbs./inch</b>	150	
<b>N/mm</b>	26	
<b>Top Cover Surface</b>	Smooth	
<b>Bottom Cover Surface</b>	Friction	
<b>Minimum Pulley Diameter, inches</b>	3	
<b>mm</b>	76	
<b>Temperature Range</b>	20° to +212°F -7° to +100°C	
<b>Special Standards</b>	USDA/FDA Approved	
<b>Cover Coefficient of Friction, Steel</b>	NA	
<b>Cardboard</b>	NA	
<b>Bottom Coefficient of Friction, Steel</b>	0.30 max	
<b>Cardboard</b>	0.32 max	
<b>Available Width(s)</b>	72'	
<b>Typical Applications</b>	Food Handling	

Phone: 800-367-0420    Email: [info@hbdthermoid.com](mailto:info@hbdthermoid.com)    [www.hbdthermoid.com](http://www.hbdthermoid.com)  
 Corporate Sales & Customer Service: 800-543-8070



## PRODUCT SPECIFICATIONS

---

*HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.*