

SHEETING – RED/BROWN NITRILE BELTING



Description:	3 PLY SCP14 R/B NBR FSXFS (S8)
Product Number	24-34-3111-722
Product Construction	Friction X Friction (Red/Brown Nitrile on Special Cotton Blend Fabric)
Color	Red/Brown
Compound Formulation	Nitrile
Fabric	Special Cotton Blend
Nominal Overall Gauge, inches	0.056 ± 0.016
mm	1.4 ± 0.4
Nominal Weight, lbs./ft²	0.38 ±10%
kg/m²	1.85 ±10%
Rated Working Tension, lbs./inch	42
N/mm	7
Top Cover Surface	Friction
Bottom Cover Surface	Friction
Minimum Pulley Diameter, in	1.5
mm	38
Temperature Range	20° to +212°F -7° to +100°C
Cover Coefficient of Friction, Steel	0.30 to 0.35 max
Cardboard	0.35 to 0.40 max
Bottom Coefficient of Friction, Steel	0.30 to 0.35 max
Cardboard	0.35 to 0.40 max
Available Width(s)	72"
Typical Applications	Wide range of industrial uses

Phone: 800-367-0420 Email: info@hbdthermoid.com www.hbdthermoid.com
 Corporate Sales & Customer Service: 800-543-8070

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.