

SLIDE-A-PACK™ BELTING



representative image

Description:	4 PLY PCB35 TAN SYN FSXFS (S8) SLIDE-A-PACK
Product Number	24-54-4111-722
Product Construction	Friction X Friction (Tan Synthetic on Polyester/Cotton Blend Fabric)
Color	Tan
Compound Formulation	Synthetic
Fabric	Polyester/Cotton Blend
Nominal Overall Gauge, inches	0.180 ± 0.020
mm	4.6 ± 0.5
Nominal Weight, lbs./ft²	0.890 ±10%
kg/m²	4.35 ±10%
Rated Working Tension, lbs./inch	140
N/mm	25
Top Cover Surface	Friction
Bottom Cover Surface	Friction
Minimum Pulley Diameter, inches	6
mm	152
Temperature Range	-30° to +180°F -34° to +82°C
Cover Coefficient of Friction, Steel	0.30 to -0.35 max
Cardboard	0.35 to -0.40 max
Bottom Coefficient of Friction, Steel	0.30 to -0.35 max
Cardboard	0.35 to -0.40 max
Available Width(s)	72"
Typical Applications	General Transmission Conveying

Phone: 800-367-0420 Email: info@hbdthermoid.com www.hbdthermoid.com
 Corporate Sales & Customer Service: 800-543-8070

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.