

SLIPTOP™ – TAN NITRILE BELTING



Description:	3 PLY PNT50 TAN NBR TDXFS (S25) SLIP TOP	
Product Number	24-29-3302-722	
Product Construction	Treated Duck X Friction (Tan Nitrile on Treated Polyester/Nylon Fabric)	
Color	Tan	
Compound Formulation	Nitrile	
Fabric	Treated Polyester	
Nominal Overall Gauge, inches	0.125 ± 0.020	
mm	3.17 ± 0.5	
Nominal Weight, lbs./ft²	0.76 ±10%	
kg/m²	3.70 ±10%	
Rated Working Tension, lbs./inch	150	
N/mm	26	
Top Cover Surface	Treated Duck	
Bottom Cover Surface	Friction	
Minimum Pulley Diameter, inches	4	
mm	101	
Temperature Range	20° to +212°F -7° to +100°C	
Cover Coefficient of Friction, Steel	NA	
Cardboard	NA	
Bottom Coefficient of Friction, Steel	0.20 max	
Cardboard	0.25 max	
Available Width(s)	72"	
Typical Applications	Package Handling	

Phone: 800-367-0420 Email: info@hbdthermoid.com www.hbdthermoid.com
 Corporate Sales & Customer Service: 800-543-8070

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.