

SLIPTOP™ – TAN NITRILE BELTING



Description:	4 PLY SCP23+ TAN NBR TDXFS (S10) SLIP TOP
Product Number	24-42-4321-722
Product Construction	Treated Duck X Friction (Tan Nitrile on Treated Polyester/Nylon Fabric)
Color	Tan
Compound Formulation	Nitrile Rubber
Fabric	Treated Polyester/Nylon
Nominal Overall Gauge, inches	0.125 ± 0.020
mm	3.2 ± 0.5
Nominal Weight, lbs./ft²	0.75 ±10%
kg/m²	3.66 ±10%
Rated Working Tension, lbs./inch	150
N/mm	26
Top Cover Surface	Treated Duck
Bottom Cover Surface	Friction
Minimum Pulley Diameter, inches	3
mm	76
Temperature Range	20° to +212°F -7° to +100°C
Cover Coefficient of Friction, Steel	0.30 max
Cardboard	0.32 max
Bottom Coefficient of Friction, Steel	0.30 to 0.35 max
Cardboard	0.35 to 0.40 max
Available Width(s)	72"
Typical Applications	Package Handling

Phone: 800-367-0420 Email: info@hbdthermoid.com www.hbdthermoid.com
 Corporate Sales & Customer Service: 800-543-8070

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.