


TEFLON* - WHITE NITRILE



Description:	3 PLY AP35 WHT NBR TEFXFS (S10) (1,2)
Product Number	24-02-3023-542
Product Construction	Teflon X Friction (White Nitrile on Polyester Fabric)
Color	White
Compound Formulation	Nitrile
Fabric	Polyester
Nominal Overall Gauge, inches	0.094 ± 0.016
mm	2.4 ± 0.4
Nominal Weight, lbs./ft²	055 ±10%
kg/m²	2.69 ±10%
Rated Working Tension, lbs./inch	105
N/mm	18
Top Cover Surface	Teflon*
Bottom Cover Surface	Friction
Minimum Pulley Diameter, inches	3
mm	76
Temperature Range	20° to +212°F -7° to +100°C
Special Standards	USDA/FDA Approved
Cover Coefficient of Friction, Steel	NA
Cardboard	NA
Bottom Coefficient of Friction, Steel	0.30 to 0.35max
Cardboard	0.35 to 0.40 max
Available Width(s)	54"
Typical Applications	Food Handling

* Teflon is a registered mark of Chemours Company.

Phone: 800-367-0420 Email: info@hbdthermoid.com www.hbdthermoid.com
 Corporate Sales & Customer Service: 800-543-8070

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.