

V-CLEAT – BLACK BELTING



Description:	3 PLY PCB35 BLK SYN V/CLXFS (S10)
Product Number	24-55-3029-722
Product Construction/Plies	V-Cleat X Friciton (Black Synthetic on Polyester/Cotton Fabric)
Color	Black
Compound Formulation	Synthetic
Fabric	Polyester/Cotton
Nominal Overall Gauge, inches	0.328 ± 0.032
mm	8.3 ± 0.80
Nominal Weight, lbs./ft2	1.22 ±10%
kg/m2	5.96 ±10%
Rated Working Tension, lbs./inch	105
N/mm	18
Top Cover Surface	Black V-Cleat
Bottom Cover Surface	Friction
Minimum Pulley Diameter, inches	4
mm	101
Temperature Range	-30° to +180°F -34° to +82°C
Cover Coefficient of Friction, Steel	NA
Cardboard	NA
Bottom Coefficient of Friction, Steel	0.20 max
Cardboard	0.25 max
Available Width(s)	72"
Typical Applications	Package Handling

Phone: 800-367-0420 Email: info@hbdthermoid.com www.hbdthermoid.com
 Corporate Sales & Customer Service: 800-543-8070

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.